

WHAT IS CLAIMED IS:

Sub
A4

1 1. A guide for a crib comprising:
2 a base with a first slot formed in said base with said
3 first slot having a periphery, a second slot formed in said
4 base and a third slot formed in said base communicating with
5 said first and said second slots, with said base having an
6 outer edge;

7 a first spring mounted on said base and disposed
8 blocking said second slot

005060" 23655960

1 2. The guide for a crib of claim 1 in which said first
2 spring comprises:

3 a cantilever spring having a first end mounted on said
4 base and a second end.

1 3. The guide for a crib of claim 2 further comprising:

2 a recess portion formed in said base disposed to
3 receive said second end of said first spring.

1 4. The guide for a crib of claim 2 further comprising:

2 a step portion formed on said second end of said first
3 spring.

Sub
A4

005050" 29655960

1 5. The guide for a crib of claim 4 further comprising:
2 a wall disposed proximate said step portion.

1 6. The guide for a crib of claim 1 further comprising a
2 ramp portion formed in said second slot.

1 7. The guide for a crib of claim 1 further comprising:
2 a T-shaped slot communicating between said first slot
3 and said outer edge.

1 8. The guide for a crib of claim 7 further comprising:
2 a second spring projecting from said base and
3 comprising an end disposed projecting into said T-shaped
4 slot.

1 9. The guide for a crib of claim 7 further comprising:
2 an aperture portion formed in said base, disposed
3 proximate and in general alignment with said end of said
4 second spring.

1 10. A crib comprising:
2 headboard,
3 a side rail,

Sub
A4

4 an elongated upper guide,
5 sliding means mounted on said side rail for
6 engagement of said upper guide;
7 a lower guide comprising:
8 a base with a first slot formed in said base with
9 said first slot having a periphery, a second slot formed in
10 said base and a third slot formed in said base communicating
11 with said first and said second slots, with said base having
12 an outer edge;
13 a first cantilever spring disposed projecting from
14 said base and disposed blocking said second slot with said
15 cantilever spring having a tip.

1 11. The crib of claim 10 further comprising:

2 a least one pin projecting from said base of said lower
3 guide and disposed engaging said headboard.

1 12. The crib of claim 10 in which said sliding means
2 mounted on said side rail comprises:

3 a pin projecting from said side rail and engaging said
4 elongated upper guide.

Sub
A4

1 13. The crib of claim 10 in which said sliding means
2 mounted on said side rail comprises:
3 a pair of flanges with said flanges engaging said
4 elongated upper guide.

1 14. The guide for a crib of claim 2 in which said first
2 spring comprises:
3 a metal cantilever spring.

1 15. The guide for a crib of claim 2 in which said first
2 spring comprises:
3 a plastic cantilever spring.

1 16. The guide for a crib of claim 1 in which said guide
2 spring comprises:
3 a plastic member.

1 17. The guide for a crib of claim 2 in which said first
2 spring comprises:
3 a leaf spring.